



## AV Cell

---

### **Mixed Hardwood round wood**

- 1. Species** Wood must be of the following specie / specie groups only:
  1. Mixed Hardwoods (Maples, Beech, Ash)
  
- 2. Length** **Preferred length is 10 feet (3.04 meter)**  
Minimum 2.54m (8 foot)  
Maximum 3.64m (12 foot)
  
- 3. Diameter** The minimum diameter of each hardwood bolt is 8cm (3 inches) inside bark  
The maximum diameter is 56cm (22 inches) inside bark
  
- 4. Sweep** No bolt shall have more than 15cm (6 inches) of sweep over its entire length (10 feet).
  
- 5. Crook** No bolt shall contain a crook or a fork.
  
- 6. Age** Wood evidently over 3 months old may be rejected.  
Bolts manufactured from dead or burnt trees are not acceptable.
  
- 7. Rot** No hardwood bolt shall contain more than 50% rot.
  
- 8. Limbs** All limbs, knots, stubs and projections shall be cut flush with the body of the bolt.
  
- 9. Load refusal** Loads that have an excessive amount of defective wood will be rejected
  
- 10. Loading quality** All loads must have a rounded top lower than the stakes.  
No cross piling, mud, brush, etc., will be allowed in the load.  
All trucks must have a minimum of four (4) solid stakes.  
Trailers loaded lengthways require 2 feet of clearance between tiers
  
- 11. Safety** Drivers will take directions from Company staff and obey all safety orders while on company property.